

<b>Model</b>	<b>: FP2SS 112M4 B3 TEFC</b>
<b>Type</b>	<b>: 3 Phase asynchronous</b>
<b>Rotor type</b>	<b>: Aluminium Squirrel Cage</b>
<b>Number of pole's</b>	<b>: 4</b>
<b>Power</b>	<b>: 4,0 kW</b>
<b>Voltage</b>	<b>: 400V / 690V +/-10%</b>

	<b>50 Hz</b>	<b>60 Hz</b>
<b>Speed</b>	1450 min-1	1740 min-1
<b>Current</b>	<b>400V Δ</b> 7,72 A <b>690V Y</b> 4,46 A	<b>480V Δ</b> 6,44 A <b>840V Y</b> 3,71 A
<b>Efficiency</b>	88,0 %	88,0 %
<b>Power factor cos φ</b> 100%	0,85	0,85
<b>Tn</b> (Nominal Torque)	26,3 Nm	22 Nm
<b>Ts</b> (Starting Torque)	57,9 Nm	48,4 Nm
<b>Tmax</b> (Maximum Torque)	61,0 Nm	51,0 Nm
<b>Is</b> (Starting Current)	<b>400V Δ</b> 51,0 A <b>690V Y</b> 29,5 A	<b>480V Δ</b> 42,0 A <b>840V Y</b> 24,6 A

<b>Weight:</b>	<b>: 55 Kg</b>
<b>IE class</b>	<b>: IE3</b>
<b>IP class</b>	<b>: IP66</b>
<b>Isolation class</b>	<b>: F (155°C)</b>
<b>Delta K</b>	<b>: 72 K</b>
<b>IEC frame</b>	<b>: IEC 112</b>
<b>Execution type</b>	<b>: B3</b>
<b>Shaft Dimensions</b>	<b>: Ø 28 j6 x 60 mm</b>
<b>Cooling</b>	<b>: TEFC - IC411 (Totally Enclosed Fan Cooled)</b>
<b>Duty Cycle:</b>	<b>: S1 100%</b>
<b>Housing material</b>	<b>: Stainless Steel AISI 304</b>
<b>Bearingshield material</b>	<b>: Stainless Steel AISI 304</b>
<b>Shaft material</b>	<b>: Stainless Steel AISI 304 (With Dertec TTS)</b>
<b>Oil seal material</b>	<b>: High Temperature NBR</b>
<b>Bearings</b>	<b>A Side (Shaft side)</b> : 6306 2RS C3 With HTWR Foodgrade Grease <b>B Side (Fan Side)</b> : 6306 2RS C3 With HTWR Foodgrade Grease
<b>Cable gland bore</b>	<b>: 2 x M25 for cable Ø between 11- 15mm)</b>
<b>Cable gland material</b>	<b>: Stainless Steel AISI 304</b>
<b>Thermal protection</b>	<b>: PTC 135 (PTC)</b> <b>: PT1 135 (Clixon / Thermal contact)</b>
<b>Certification</b>	<b>: UL &amp; CE</b>
<b>Taric Code</b>	<b>: 8501200090</b>
<b>Country of origin</b>	<b>: The Netherlands</b>